



XEIKON 3000 SERIES

Top performers in digital printing
Xeikon 3030PLUS -
Xeikon 3300 - Xeikon 3500

LABELS

The Xeikon 3030Plus, Xeikon 3300 and the Xeikon 3500 are the top end of the Xeikon 3000 Series. They excel in productivity and high quality printing. Where the award winning Xeikon 3300 and Xeikon 3030Plus are built around the commonly used 330 mm or 13" web width, the Xeikon 3500 allows the use of material up to 516 mm or 20,3", making it the most productive digital label press.



XEIKON 3030PLUS XEIKON 3300 XEIKON 3500 specifications

THE UNIQUENESS OF THE XEIKON 3000 SERIES IS IN ITS COMBINATION OF PRODUCTIVITY AND QUALITY BENEFITS

- High productivity by full rotary printing independent of either the number of colors or the repeat length of the job.
- Print resolution: true 1200 dpi with variable dot density
- Variable printing width and length
- QA-I or ICE dry toner
 - Allowing the use of substrate without specific pre-treatment
 - High light fastness
 - Meeting FDA regulations regarding food contact
 - One-pass opaque white
 - No VOC emission
- Easy integration in any workflow software solution
- Professional color management
- Expert consultancy and service

XEIKON

XEIKON INTERNATIONAL BV

T. +31 (0)117 37 50 20 - F. +31 (0)117 37 50 21
Brievsstraat 70 - 4529 GZ Eede - the Netherlands
www.xeikon.com - info@xeikon.com

3030PLUS33003500_ENG_083017_spec

© 2016 Xeikon International BV. All rights reserved. All trademarks are property of their respective owners. No parts of this brochure may be reproduced, copied, adapted, translated or transmitted in any form or by any means, without prior written permission from Xeikon. The material in this brochure is for informational purposes only and is subject to change without prior notice. No responsibility or liability is assumed by Xeikon for any errors, which may appear in this brochure.

PRINT TECHNOLOGY & FEATURES	
Process	LED-array-based, dry toner electrophotography. Full rotary, variable repeat length
Color configuration	5/0 simplex, 5 th color station for spot color, security toner or opaque white
Standard color sequence	White (5 th), Yellow, Cyan, Magenta, Black (sequence can be altered for other applications)
In-line density control	Standard, automatic density control while printing
In-line register control	Standard, automatic register control while printing
TONER SYSTEM	
Toner	Xeikon QA-I and ICE dry toner. Pantone® licensed Meeting FDA regulation and Nestle guidelines for Food contact (ISEGA approved)
Special colors	Spot colors: R-G-B, Orange, ExtraMagenta, Clear (UV reflecting), SuperBlack, White MatteSilver and Palladiumsilver
Light fastness	6-8 on blue wool scale
PRINT MEDIA	
Pre-printed stock functionality	Synchronising on a preprinted stock, front or back
Web-fed	SA or PS label (paper, PP, PE, PET, vinyl, co-extruded film) paper, paperboard, transfer substrate, unsupported BoPP and oPP film for IML
Media width	Xeikon 3300: 200 - 330 mm (7,9" - 13,0") Xeikon 3300PLUS: 200 - 330 mm (7,9" - 13,0") Xeikon 3500: 250 - 516 mm (9,8" - 20,3")
Media weight	40 - 350 gsm (27 lb text to 122 lb cover)
Media caliper	40 - 550 µm (1,6 mil - 21,65 mil)
Web alignment	Active web alignment standard. Suited for paper and synthetic (white, clear) substrates
PRESS THROUGHPUT	
Web speed	All engines: 9,6 m/min (31,5 ft/min) up to 350 gsm All engines: 15,0 m/min (49,2 ft/min) up to 300 gsm Excl. Xeikon 3030PLUS: 19,2 m/min (63,0 ft/min) up to 250 gsm
Printing speed	Xeikon 3300: 380 sqm/hr (589 MSI/hr) Xeikon 3500: 594 sqm/hr (921 MSI/hr) Xeikon 3030PLUS: 297 sqm/hr (460 MSI/hr)
IMAGING	
Resolution	1200 dpi with variable dot density
Screening	Pericles screening library up to 240 lpi
Imaging width	Xeikon 3300: 322 mm (12,7") Xeikon 3030PLUS: 322 mm (12,7") Xeikon 3500: 508 mm (20")
Repeat length	Variable (0 - 55 m, 0 - 180 ft)
Digital front-end	Xeikon X-800
Compliance	CE, CB, FCC Deinkability (Ingede)
PERIPHERAL EQUIPMENT, UPGRADES AND SERVICES (Optional)	
Unwinder	PMS: max. 100 kg (220 lbs), max. 600 mm (23.6") diameter PMS Large: max. 850 kg (1,870 lbs), max 1,5 m (59") diameter
Rewinder	Selection of solutions available: rewinders, converters, stackers, inline varnish
Cutter	Minimum cut length: 330 mm (13") during printing Cutter accuracy: ± 200 µm (± 7,87 mil) initiated by printed marker
Speed upgrade	Xeikon 3030Plus: 19,2 m/min (63,0 ft/min)
Width upgrade	Xeikon 3030Plus: 508 mm (20") Xeikon 3300: 508 mm (20")

direct. dedicated. digital.